
LTS 531 24/1

LED Insert designed for MAGIC Low Voltage System with lens optic Extremelly cut-off design max. 24W max. 1650lm CCT=3000K as a standard another CCT or request

CRI(Ra) >90 as a standard another CRI(Ra) [80/97] on request MacAdam 3 L90B10 @60.000h 5 years guarantee 48V DC/DC 4 wire adapter installed ON/OFF | 1-10V | DALI | CASAMBI White/Black 0,44kg





Туре CRI+CCT * Reflector Dimming Colour LTS 531 24/1 LED 930 ON/OFF WH (WHITE) 24° 927 [on request] 36° [on request] 1-10V BL (BLACK) 935 [on request] DALI 940 [on request] CASAMBI

* - other versions like CRISP WHITE, PREMIUM WHITE, CLEAR WHITE, MEAT etc. also possible Order example: TDS 319 1/29 LED930 36DEG ON/OFF WHITE

Туре	COB Power [W]	Luminaire Power [W]	COB Flux* [lm]	Luminaire Flux* [Im]
LTS 531 24/1 LED930	24	24	2880	1650

Based on CCT=3000K CRI(Ra)>90



Power, Luminous Flux and CCT depending on customer need; current detail technical data on website www.sentinel.pl Power & Luminous flux tolerance +/-10%. Driverless versions on request.